



GUARDIANDOORS.COM

0800 783 6602

ROLLER SHUTTERS - SECTIONAL OVERHEAD DOORS - INSULATED DOORS - FOLDING DOORS
STEEL DOORS - FIRE RATED DOORS - SECURITY DOORS - SLIDING GATES - HIGH SPEED DOORS

Fire-resistant roller shutter Insulation 60 (EI) Fire resistance 60 (EW)

Fire-resistant roller shutters offer an excellent solution for closing off or compartmentalising premises such as government agencies, shopping malls and, of course, various industrial applications in a fire-safe manner.

Partly thanks to its high fire-resistance of 60 minutes (in accordance with the EI(1) requirement) and even 180 minutes (in accordance with the EW requirement), based on two-sided testing in accordance with EN 1634-1.

The fire-resistant roller shutter is also available with a certified liquid barrier, explosion-proof (ATEX) components and is even available entirely ATEX marked, so that the shutter provides an excellent solution for areas where hazardous substances are stored.

The fire-resistant roller shutter has successfully undergone two sided smoke resistance testing in accordance with EN 1634-3 at both Sa 20 (cold smoke at approx. 20 degrees Celsius) and Sm 200 (hot smoke at approx. 200 degrees Celsius).

Curtain construction The door curtain of the fire-resistant roller shutter is constructed from 60 mm thick galvanised, double walled steel slats. The slats consist of two 0.80 mm thick profiled, galvanised steel sheets, filled with mineral insulation. The underside of the curtain is finished with a galvanised steel L-profile, attached to the bottom slat of the curtain by steel rivets. The slats are finished with galvanised steel end locks on both sides. The slats are fitted with a unique click-system that allows the slats to be mounted and unmounted at a 90 degree angle.

Side guide The side guides are constructed from galvanised steel guides and a corner section, which are both fitted with intumescent material.

Movement system The movement system is composed of two galvanised steel brackets on which the tube is mounted. The brackets are fastened to the wall with bolts and locking plates. To ensure the stability of the movement system, a galvanised steel diagonal brace is fitted to the ends of the brackets. The drive shaft that rolls the curtain up and down is located between the brackets. System of operations The fire-resistant roller shutters come standard with a 400 V chain wheel motor. If the dimensions of the fire-resistant roller shutter are small, a 230V tubular motor can be fitted. The roller shutters are fitted with a control unit and safety brake as standard. If the fire-resistant roller shutter is fitted with a chain wheel motor, an optional fail-safe drive system can be installed to close the shutter in a controlled manner using gravity, in the event of power failure. For fire-resistant roller shutters with a tubular motor, an emergency backup battery can be optionally installed to allow the shutter to continue operating in the event of power failure.

Control As standard, the fire-resistant roller shutters are fitted with a control box which can accommodate various types of control devices such as key switches, smoke or temperature detectors and a fire alarm system, if present.

Optional features The fire-resistant roller shutter can optionally be fitted with a galvanised steel roller and/or motor enclosure. All steel components of the fire-resistant roller shutters can be coated in any desired RAL colour. All visible steel components (with the exception of the curtain) can also be manufactured in 304 or 316 stainless steel. The electrical components (drive system and control unit) and any accessories (safety brake, on-stop-down switch) can be supplied in an explosion proof (ATEX) construction. The entire fire-resistant roller shutter can optionally be provided with ATEX marking. The shutters can also be supplied with a certified liquid barrier. The shutters have also successfully undergone two-sided smoke resistance testing in accordance with EN 1634-3. The fire-resistant roller shutter can also be supplied with certification for soundproofing of up to 37 dB, tested in accordance with ISO 10140-2:2010.



Classification	Fire rating	max. width	max. height	max. opening
EI(1)	60 minutes	10.000 mm	10.000 mm	50 m2
EW	60 minutes	10.000 mm	10.000 mm	50 m2

