



L20 Doors/ Shutters/ Hatches
610 Roller shutter doors
Specification Text

Supplier:

Guardian Sliding Grilles – Trading name for GUARDIAN INDUSTRIAL DOORS LTD 45 Progress Road Leigh On Sea Essex, SS9 5PR Tel: 01702 512424. Fax: 01702 260117. Email: mail@slidingfoldinggrilles.co.uk Web: <http://slidingfoldinggrilles.co.uk/>

Product reference:

ECO WAVE Sliding Folding Grille

Arrangement:

Side acting top hung sliding folding Grille

Construction:

Curtain constructed from 6063 T5 aluminum alloy and shall incorporate 51 mm high truss-like plates at the top and bottom of the closure. 8 mm diameter vertical rods on 89 mm centers are linked by flat horizontal bars 3 mm by 16 mm by 197 mm. Bars are vertically spaced every 305 mm with 11mm diameter sleeves over alternating rods. Optional spacing of 229 mm, 152 mm and 76 mm are available.

Track and Trolleys:

Track: 33 wide x 46 mm high thick extruded aluminum section with continuous recess for splice tongues and pins. Standard curves are available with 254mm or 356mm radii. Custom radius curved track is available to suite most conditions.

Trolleys: 29 mm diameter nylon tired ball bearing wheels; two wheel assembly at each hanger; three wheel assembly at all vertical members

Finish as delivered:

Standard factory finishes is 10 micron clear anodizing and stainless steel version available.

Operation:

Manual Push / pull operation.

Locking Options:

The grille incorporates 33mm x 60mm vertical posts spaced not to exceed 3,000 mm on center and located at each curve. Lead posts utilize concealed, masterkeyable cylinder operated hook-bolt with lock operable from both sides of curtain or optional thumb turn cylinder lock operable from tenant side of curtain that engages a full height wall channel. Intermediate posts provided with concealed, masterkeyable cylinder operated bottom ratcheted drop bolts with lock operable from interior or exterior side of the opening. Posts with drop bolts include dust proof stainless steel floor sockets.

The locking knobs are manufactured of heavy-duty aluminum construction.

The locking posts have a unique self-adjusting locking rod with (6) different positions of adjustments to allow for deflections in bulkheads and irregularities in finished flooring. The quick-connect locking post is also exclusive to Cornell grilles and closures. This post allows replacing or servicing of the locking post without removing the entire door. Also lead and end posts have special softly padded astragals that prevent damage too adjacent finished such as glass or mirror pocket doors and columns.

Weight and Stacking:

Grille weight is approximately 5.9 kg/square metre. Minimum stacking is 87.5mm/metre of opening plus 89mm per locking member (consult factory for critical project specific stack dimensions)

The structural support must be capable of carrying the weight of a fully stacked door at any point along its length.

Optional accessories:

Pocket Doors: Factory supplied pocket doors are an available option with all side-folding units. Pocket doors stop at underside of track and look better aesthetically when the track is recessed in the ceiling or soffit. Pocket doors and frames are fabricated from A36 HR steel, USS 12-gauge. Hinges are 76.2 mm non-mortise type. Lock is a 25.4 mm security mortise cylinder. Standard finish is a phosphate treatment followed by a light gray baked-on polyester powder coat; minimum 0.065 mm cured film thickness. Optional RAL colors are available.

Standard Warranty:

1 year from date of installation against defects in material and workmanship.